

## **DECLARATION OF PERFORMANCE AND CONFORMITY:** EN 10088-4:2009

Document no.:

TEC-DOP-4404C

Revision 5

For the construction products: Cold Rolled Strip & Sheet of Corrosion Resisting Steel					
1.	Identification code of the product-type		1.4404 – EN 10088-4:2009		
2.	Type		1.4404 See marking / label / inspection certificate		
3.	Intended use		Building Construction or Civil Engineering		
			Columbus Stainless (Pty) Ltd		
4.	Manufacturer		Hendrin	Hendrina Road, Middelburg, South Africa,	
			1050		
5.	Authorised Representative in the EU		Acerinox Europa S.A.U. C/ Santiago de		
3.	·		Compostela nº 100. 28035 Madrid, Spain		
ll 6.	Assessment system and verification for		EN 10088-4, Annex ZA, System 2+		
<u>U.</u>	constancy of performance as p	er Annex V			
	The Notified Body:	_	TÜV Rheinland Industrie Service GmbH, Koln		
	has conducted the first inspection and				
_	continuous surveillance according to the		2+ 0035-CPR-A304		
7.	system:				
	and issued the certificate:	for the feeten	0035-CP	R-A304	
	as a confirmation of conformity	for the factory			
8.	production control  Construction product with European Technical Assessment: No				
9.					
	- 416 414	5 (			
	Essential Characteristics	Performa		Harmonised Technical Specification	
$\vdash$	Tolerances on Dimensions	Tables 1, 2, 3	& 4	-	
	Tolerances on Dimensions and Shape		& 4	Harmonised Technical Specification ISO 9445-2:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties -	Tables 1, 2, 3	& 4	-	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:	Tables 1, 2, 3 o Paragraphs 11	& 4	-	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength	Tables 1, 2, 3 of Paragraphs 11	& 4	-	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength	Tables 1, 2, 3 of Paragraphs 11  530-680MPa ≥240MPa	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation	Tables 1, 2, 3 of Paragraphs 11  530-680MPa ≥240MPa ≥40%	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength	Tables 1, 2, 3 of Paragraphs 11  530-680MPa ≥240MPa ≥40% N/A	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by	Tables 1, 2, 3 of Paragraphs 11  530-680MPa ≥240MPa ≥40%	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition]	Tables 1, 2, 3 of Paragraphs 11  530-680MPa ≥240MPa ≥40% N/A  Table 3	& 4	ISO 9445-2:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by	Tables 1, 2, 3 of Paragraphs 11  530-680MPa ≥240MPa ≥40% N/A	& 4	ISO 9445-2:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition]	Tables 1, 2, 3 of Paragraphs 11  530-680MPa ≥240MPa ≥40% N/A  Table 3	& 4	ISO 9445-2:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:	Tables 1, 2, 3 of Paragraphs 11  530-680MPa ≥240MPa ≥40% N/A  Table 3  Table 3	& 4	ISO 9445-2:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact	Tables 1, 2, 3 of Paragraphs 11  530-680MPa ≥240MPa ≥40% N/A  Table 3	& 4	ISO 9445-2:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength  Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]  Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1, 2, 3 of Paragraphs 11  530-680MPa ≥240MPa ≥40% N/A  Table 3  Table 3  Table 10	& 4	ISO 9445-2:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact	Tables 1, 2, 3 of Paragraphs 11  530-680MPa ≥240MPa ≥40% N/A  Table 3  Table 3	& 4	ISO 9445-2:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength  Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]  Fracture Toughness / Brittle Strength [Covered by impact strength]  Cold Formability [Covered by	Tables 1, 2, 3 of Paragraphs 11  530-680MPa ≥240MPa ≥40% N/A  Table 3  Table 3  Table 10	& 4 , 12 & 13	ISO 9445-2:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	

10. The performance of the product is in accordance with the specification given above. This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical Signed at Middelburg, South Africa on the 12<sup>th</sup> day of June 2020