

## **DECLARATION OF PERFORMANCE AND CONFORMITY:** EN 10088-4:2009

Document no.:

TEC-DOP-4404H

Revision 6

| For the construction products: Hot Rolled Strip & Sheet of Corrosion Resisting Steel |  |   |  |   |  |
|--|--|---|--|---|--|
| 1.   | , , , ,  |   |  | 1.4404 – EN 10088-4:2009  |  |
| 2.   | Type   |   | 1.4404 See marking / label / inspection certificate                          |   |  |
| 3.   | Intended use   |   | Building Construction or Civil Engineering                                   |   |  |
|  |  |   |  | us Stainless (Pty) Ltd  |  |
| 4.   | Manufacturer   |   | Hendrina Road, Middelburg, South Africa,                                     |   |  |
|  |  |   | 1050   |   |  |
| 5.   | Authorised Representative in the EU  |   | Acerinox Europa S.A.U. C/ Santiago de Compostela nº 100. 28035 Madrid, Spain |   |  |
| 6.   | Assessment system and verification for constancy of performance as per Annex V   |   | EN 10088-4, Annex ZA, System 2+  |   |  |
|  | The Notified Body:   |   | TÜV Rheinland Industrie Service GmbH, Koln                                   |   |  |
|  | has conducted the first inspect  | ion and   |  | , , ,   |  |
|  | continuous surveillance according to the   |   | 2+<br>0035-CPR-A304  |   |  |
| 7.   | system:  |   |  |   |  |
|  | and issued the certificate:  |   |  |   |  |
|  | as a confirmation of conformity  | for the factory   |  |   |  |
|  | roduction control  |   |  |   |  |
| 8.   |  |   |  |   |  |
| 9.   |  |   |  |   |  |
|  | Essential Characteristics  | Performa  | nce  | Harmonised Technical Specification  |  |
|  | Tolerances on Dimensions   | Tables 1 to 10<br>Paragraphs 9, 10 & 11                     |  | EN 10051:2010   |  |
|  |  | Paragraphs 9  | 1በ ጼ 11  | EN 10051:2010   |  |
|  | and Shape  Mechanical Properties -   | Paragraphs 9,   | 10 & 11  | EN 10051.2010   |  |
|  | Mechanical Properties -  | Paragraphs 9,   | 10 & 11  | EN 10051.2010   |  |
|  | Mechanical Properties -<br>Transverse:   | Paragraphs 9,<br>530-680MPa                                 | 10 & 11  |   |  |
|  | Mechanical Properties - Transverse:  • Tensile strength  |   | 10 & 11  | EN 10031.2010<br>EN 10088-4:2009  |  |
|  | Mechanical Properties -<br>Transverse:   | 530-680MPa  | 10 & 11  |   |  |
|  | Mechanical Properties - Transverse:  | 530-680MPa<br>≥220MPa                                       | 10 & 11  |   |  |
|  | Mechanical Properties - Transverse:  | 530-680MPa<br>≥220MPa<br>≥40%<br>≥60J                       | 10 & 11  | EN 10088-4:2009   |  |
|  | Mechanical Properties - Transverse:      Tensile strength     0.2% Proof strength     Elongation     Impact strength Weldability [Covered by chemical composition]   | 530-680MPa<br>≥220MPa<br>≥40%                               | 10 & 11  |   |  |
|  | Mechanical Properties - Transverse:  | 530-680MPa<br>≥220MPa<br>≥40%<br>≥60J<br>Table 3            | 10 & 11  | EN 10088-4:2009 EN 10088-4:2009   |  |
|  | Mechanical Properties - Transverse:  | 530-680MPa<br>≥220MPa<br>≥40%<br>≥60J                       | 10 & 11  | EN 10088-4:2009   |  |
|  | Mechanical Properties - Transverse:  | 530-680MPa<br>≥220MPa<br>≥40%<br>≥60J<br>Table 3            | 10 & 11  | EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009                                   |  |
|  | Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact | 530-680MPa<br>≥220MPa<br>≥40%<br>≥60J<br>Table 3            | 10 & 11  | EN 10088-4:2009 EN 10088-4:2009   |  |
|  | Mechanical Properties - Transverse:  | 530-680MPa<br>≥220MPa<br>≥40%<br>≥60J<br>Table 3<br>Table 3 | 10 & 11  | EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009                                   |  |
|  | Mechanical Properties - Transverse:  | 530-680MPa<br>≥220MPa<br>≥40%<br>≥60J<br>Table 3            | 10 & 11  | EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009                                   |  |
|  | Mechanical Properties - Transverse:  | 530-680MPa<br>≥220MPa<br>≥40%<br>≥60J<br>Table 3<br>Table 3 |  | EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009 |  |

10. The performance of the product is in accordance with the specification given above. This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical Signed at Middelburg, South Africa on the 12<sup>th</sup> day of June 2020