

DECLARATION OF PERFORMANCE AND CONFORMITY: EN 10088-4:2009

Document no.:

TEC-DOP-4435C

Revision 5

For the construction products: Cold Rolled Strip & Sheet of Corrosion Resisting Steel					
1.	Identification code of the products.			EN 10088-4:2009	
2.	Type	ici-type	1.4435 See marking / label / inspection certificate		
3.			Building Construction or Civil Engineering		
<u> </u>			Columbus Stainless (Pty) Ltd		
4.	Manufacturer		Hendrina Road, Middelburg, South Africa,		
	Manaraotaron	1050		a Road, Middelburg, Oodin Ainea,	
			Acerinox Europa S.A.U. C/ Santiago de		
5.	Authorised Representative in the	he EU	Compostela nº 100. 28035 Madrid, Spain		
	Assessment system and verific	cation for	EN 10088-4, Annex ZA, System 2+		
6.	constancy of performance as p				
	The Notified Body:		TÜV Rheinland Industrie Service GmbH, Koln		
	has conducted the first inspect				
	continuous surveillance accord	ling to the	_		
7.			2+	5 4 4 4 4	
	and issued the certificate:	() () ()	0035-CP	R-A304	
	as a confirmation of conformity	for the factory			
0	Production control				
<u>8.</u> 9.	Construction product with European Technical Assessment: No Declared Performance:				
		Deuferner		Use a stand Table is all One altic attac	
	Essential Characteristics	Performa		Harmonised Technical Specification	
	Tolerances on Dimensions	Tables 1, 2, 3	& 4		
	Tolerances on Dimensions and Shape		& 4	Harmonised Technical Specification ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties -	Tables 1, 2, 3	& 4		
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1, 2, 3 Paragraphs 11	& 4		
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength	Tables 1, 2, 3 Paragraphs 11 550-700MPa	& 4		
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength	Tables 1, 2, 3 Paragraphs 11 550-700MPa ≥240MPa	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation	Tables 1, 2, 3 Paragraphs 11 550-700MPa ≥240MPa ≥40%	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength	Tables 1, 2, 3 Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A	& 4	ISO 9445-2:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by	Tables 1, 2, 3 Paragraphs 11 550-700MPa ≥240MPa ≥40%	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength	Tables 1, 2, 3 Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength • 0.2% Proof strength Elongation • Impact strength• Impact strength Weldability [Covered by chemical composition]	Tables 1, 2, 3 Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A	& 4	ISO 9445-2:2009 EN 10088-4:2009	
	Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength• 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle	Tables 1, 2, 3 Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A Table 3 Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength• 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle Strength [Covered by impact	Tables 1, 2, 3 Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength• 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1, 2, 3 Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A Table 3 Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength• 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle Strength [Covered by impact strength]Cold Formability [Covered by	Tables 1, 2, 3 Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A Table 3 Table 3 Table 10	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength• 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1, 2, 3 Paragraphs 11 550-700MPa ≥240MPa ≥40% N/A Table 3 Table 3	& 4 , 12 & 13	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	

10. The performance of the product is in accordance with the specification given above.

This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical Signed at Middelburg, South Africa on the 12th day of June 2020