

## DECLARATION OF PERFORMANCE AND CONFORMITY: EN 10088-4:2009

Document no.:

TEC-DOP-4436H

Revision 6

For the construction products: Hot Rolled Strip & Sheet of Corrosion Resisting Steel					
1.			1.4436 – EN 10088-4:2009		
2.	Туре		1.4436 See marking / label / inspection certificate		
3.	Intended use		Building Construction or Civil Engineering		
				us Stainless (Pty) Ltd	
4.	Manufacturer			ndrina Road, Middelburg, South Africa,	
			1050		
5.	Authorised Representative in the	he FII	Acerinox Europa S.A.U. C/ Santiago de		
J.	·	Composi		tela nº 100. 28035 Madrid, Spain	
6.	Assessment system and verific		nex V EN 10088-4, Annex ZA, System Z+		
	constancy of performance as p	er Annex V			
	The Notified Body:		TÜV Rheinland Industrie Service GmbH, Koln  2+ 0035-CPR-A304		
	has conducted the first inspection and				
7.	continuous surveillance according to the				
	system: and issued the certificate:				
	as a confirmation of conformity for the factory				
	production control				
8.	Construction product with European Technical Assessment: No				
9. Declared Performance:					
	<b>Essential Characteristics</b>	Performa	nce	Harmonised Technical Specification	
	Essential Characteristics Tolerances on Dimensions	Performa Tables 1 to 10	ince	-	
	Tolerances on Dimensions	Tables 1 to 10		Harmonised Technical Specification EN 10051:2010	
				-	
	Tolerances on Dimensions and Shape	Tables 1 to 10		-	
	Tolerances on Dimensions and Shape  Mechanical Properties -	Tables 1 to 10		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9,		-	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength	Tables 1 to 10 Paragraphs 9, 550-700MPa ≥220MPa ≥40%		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength	Tables 1 to 10 Paragraphs 9, 550-700MPa ≥220MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation	Tables 1 to 10 Paragraphs 9, 550-700MPa ≥220MPa ≥40% ≥60J		EN 10051:2010  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition]	Tables 1 to 10 Paragraphs 9, 550-700MPa ≥220MPa ≥40%		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by	Tables 1 to 10 Paragraphs 9,  550-700MPa ≥220MPa ≥40% ≥60J  Table 3		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]	Tables 1 to 10 Paragraphs 9, 550-700MPa ≥220MPa ≥40% ≥60J		EN 10051:2010  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9,  550-700MPa ≥220MPa ≥40% ≥60J  Table 3  Table 3		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9,  550-700MPa ≥220MPa ≥40% ≥60J  Table 3		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength  Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]  Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9,  550-700MPa ≥220MPa ≥40% ≥60J  Table 3  Table 3		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength  Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]  Fracture Toughness / Brittle Strength [Covered by impact strength]  Cold Formability [Covered by	Tables 1 to 10 Paragraphs 9,  550-700MPa ≥220MPa ≥40% ≥60J  Table 3  Table 3		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength  Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]  Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9,  550-700MPa ≥220MPa ≥40% ≥60J  Table 3  Table 3  Table 10	10 & 11	EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	

10. The performance of the product is in accordance with the specification given above. This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical

Signed at Middelburg, South Africa on the 12<sup>th</sup> day of June 2020