

DECLARATION OF PERFORMANCE AND CONFORMITY: EN 10088-4:2009

Document no.:

TEC-DOP-4521C

Revision 5

| For the construction products: Cold Rolled Strip & Sheet of Corrosion Resisting Steel | | | | | |
|---|--|--|---|--|--|
| 1. | Identification code of the products: | | | EN 10088-4:2009 | |
| 2. | Type | | 1.4521 See marking / label / inspection certificate | | |
| 3. | | | Building Construction or Civil Engineering | | |
| <u> </u> | | | Columbus Stainless (Pty) Ltd | | |
| 4. | Manufacturer | | | Hendrina Road, Middelburg, South Africa, | |
| <u> </u> т. | Manaractarer | | 1050 | a road, middelbarg, Oodin Amea, | |
| | | | | Acerinox Europa S.A.U. C/ Santiago de | |
| 5. | Authorised Representative in the | EU Compostela nº 100. 28035 Madrid, Spain | | | |
| | Assessment system and verific | ation for | EN 10088-4, Annex ZA, System 2+ | | |
| 6. | constancy of performance as p | | | | |
| | The Notified Body: | | TÜV Rheinland Industrie Service GmbH, Koln | | |
| | has conducted the first inspection and | | | | |
| | continuous surveillance accord | ling to the | | | |
| 7. | | | 2+ | | |
| | and issued the certificate: | | 0035-CP | R-A304 | |
| | as a confirmation of conformity | for the factory | | | |
| | production control | | | | |
| 8. | Construction product with European Technical Assessment: No | | | | |
| 9. Declared Performance: | | | | | |
| | | | | | |
| | Essential Characteristics | Performa | | Harmonised Technical Specification | |
| | Tolerances on Dimensions | Tables 1, 2, 3 | & 4 | | |
| | Tolerances on Dimensions and Shape | | & 4 | Harmonised Technical Specification ISO 9445-2:2009 | |
| | Tolerances on Dimensions and Shape Mechanical Properties - | Tables 1, 2, 3 | & 4 | | |
| | Tolerances on Dimensions and Shape Mechanical Properties - Transverse: | Tables 1, 2, 3 Paragraphs 11 | & 4 | | |
| | Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength | Tables 1, 2, 3 Paragraphs 11 420-640MPa | & 4 | | |
| | Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength | Tables 1, 2, 3 Paragraphs 11 420-640MPa ≥320MPa | & 4 | ISO 9445-2:2009 | |
| | Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation | Tables 1, 2, 3 √ Paragraphs 11 420-640MPa ≥320MPa ≥20% | & 4 | ISO 9445-2:2009 | |
| | Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength | Tables 1, 2, 3 √ Paragraphs 11 420-640MPa ≥320MPa ≥20% N/A | & 4 | ISO 9445-2:2009 EN 10088-4:2009 | |
| | Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by | Tables 1, 2, 3 √ Paragraphs 11 420-640MPa ≥320MPa ≥20% | & 4 | ISO 9445-2:2009 | |
| | Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength • 0.2% Proof strength Elongation • Impact strength• Impact strength Weldability [Covered by chemical composition] | Tables 1, 2, 3 4 Paragraphs 11 420-640MPa ≥320MPa ≥20% N/A Table 1 | & 4 | ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 | |
| | Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by | Tables 1, 2, 3 √ Paragraphs 11 420-640MPa ≥320MPa ≥20% N/A | & 4 | ISO 9445-2:2009 EN 10088-4:2009 | |
| | Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength• 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by | Tables 1, 2, 3 4 Paragraphs 11 420-640MPa ≥320MPa ≥20% N/A Table 1 | & 4 | ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 | |
| | Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength • 0.2% Proof strength Elongation • Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition] | Tables 1, 2, 3 4 Paragraphs 11 420-640MPa ≥320MPa ≥20% N/A Table 1 | & 4 | ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 | |
| | Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength• 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle Strength [Covered by impact strength] | Tables 1, 2, 3 √ Paragraphs 11 420-640MPa ≥320MPa ≥20% N/A Table 1 Table 1 | & 4 | ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 | |
| | Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength• 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle Strength [Covered by impact strength]Cold Formability [Covered by | Tables 1, 2, 3 √ Paragraphs 11 420-640MPa ≥320MPa ≥20% N/A Table 1 Table 1 Table 7 | & 4 | ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 | |
| | Tolerances on Dimensions and ShapeMechanical Properties - Transverse:• Tensile strength• 0.2% Proof strength Elongation• Impact strengthWeldability [Covered by chemical composition]Durability [Covered by chemical composition]Fracture Toughness / Brittle Strength [Covered by impact strength] | Tables 1, 2, 3 √ Paragraphs 11 420-640MPa ≥320MPa ≥20% N/A Table 1 Table 1 | & 4 , 12 & 13 | ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 | |

10. The performance of the product is in accordance with the specification given above.

This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical Signed at Middelburg, South Africa on the 12th day of June 2020