

DECLARATION OF PERFORMANCE AND CONFORMITY: EN 10088-4:2009

Document no.:

TEC-DOP-4571C

Revision 5

For the construction products, Cold Polled Strip 9 Sheet of Correction Desisting Steel					
For the construction products: Cold Rolled Strip & Sheet of Corrosion Resisting Steel					
1.				1.4571 – EN 10088-4:2009	
2.			1.4571 See marking / label / inspection certificate		
3.	Intended use		Building Construction or Civil Engineering		
				nbus Stainless (Pty) Ltd	
4.	Manufacturer			a Road, Middelburg, South Africa,	
			1050		
5.	Authorised Representative in tl	ho FU	Acerinox Europa S.A.U. C/ Santiago de		
<u> </u>	•		Compostela nº 100. 28035 Madrid, Spain		
6.	Assessment system and verification for		EN 10088-4, Annex ZA, System 2+		
<u> </u>	constancy of performance as per Annex V				
	The Notified Body:		TÜV Rheinland Industrie Service GmbH, Koln		
	has conducted the first inspection and				
	continuous surveillance according to the		2.		
7.	system:		2+	D 4204	
	and issued the certificate:	for the feators	0035-CP	R-A304	
	as a confirmation of conformity	for the factory			
8.	production control				
9.	Declared Performance:				
<u> </u>					
		Device		Hammania al Taskaisal On aski astisa	
	Essential Characteristics	Performa		Harmonised Technical Specification	
	Tolerances on Dimensions	Tables 1, 2, 3	& 4		
	Tolerances on Dimensions and Shape		& 4	Harmonised Technical Specification ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties -	Tables 1, 2, 3	& 4		
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1, 2, 3 Paragraphs 11	& 4		
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength	Tables 1, 2, 3 Paragraphs 11 540-690MPa	& 4		
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength	Tables 1, 2, 3 Paragraphs 11 540-690MPa ≥240MPa	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation	Tables 1, 2, 3 √ Paragraphs 11 540-690MPa ≥240MPa ≥40%	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength	Tables 1, 2, 3 Paragraphs 11 540-690MPa ≥240MPa	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by	Tables 1, 2, 3 √ Paragraphs 11 540-690MPa ≥240MPa ≥40%	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition]	Tables 1, 2, 3 4 Paragraphs 11 540-690MPa ≥240MPa ≥40% N/A Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by	Tables 1, 2, 3 √ Paragraphs 11 540-690MPa ≥240MPa ≥40% N/A	& 4	ISO 9445-2:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition]	Tables 1, 2, 3 4 Paragraphs 11 540-690MPa ≥240MPa ≥40% N/A Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle	Tables 1, 2, 3 4 Paragraphs 11 540-690MPa ≥240MPa ≥40% N/A Table 3 Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact	Tables 1, 2, 3 4 Paragraphs 11 540-690MPa ≥240MPa ≥40% N/A Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1, 2, 3 4 Paragraphs 11 540-690MPa ≥240MPa ≥40% N/A Table 3 Table 3 Table 10	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength] Cold Formability [Covered by	Tables 1, 2, 3 4 Paragraphs 11 540-690MPa ≥240MPa ≥40% N/A Table 3 Table 3	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1, 2, 3 4 Paragraphs 11 540-690MPa ≥240MPa ≥40% N/A Table 3 Table 3 Table 10	& 4 , 12 & 13	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	

10. The performance of the product is in accordance with the specification given above.

This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical Signed at Middelburg, South Africa on the 12th day of June 2020